

INSTALLATION INSTRUCTIONS

Ibiza Toilet with Tank | Product code: BAT4501

Before you begin

Installation must be completed by a competent installer in accordance with local building and plumbing requirements. Inspect the WC and compare it with the current technical specification before fitting. Do not install a damaged product.

Confirm the installation

This is a floor-standing close-coupled WC with a supplied cistern and dual-flush mechanism. Confirm the soil connection, water inlet, service clearances and finished floor are suitable for the 600 x 360 x 780 mm product.

- 1 Plan services. Verify the selected horizontal or vertical outlet arrangement, connector, water inlet position and isolation-valve access.
- 2 Dry-fit the pan. Position it level on the finished floor, confirm the cistern-to-pan alignment and mark only verified fixing locations.
- 3 Connect the outlet. Fit the correct pan connector without strain, distortion or obstruction; follow the connector manufacturer's instructions.
- 4 Secure the pan. Use suitable mechanical floor fixings where specified and neutral-cure sanitary silicone as a seal, without point-loading or over-tightening the porcelain.
- 5 Assemble the cistern. Fit the supplied seals and dual-flush mechanism, then secure the cistern evenly to the pan. Do not over-tighten porcelain connections.
- 6 Connect and commission. Connect the isolated water supply, adjust the mechanism, fill and flush repeatedly. Check every joint for leaks and confirm both flush settings operate correctly.
- 7 Fit and adjust the supplied soft-close seat and cover. Allow sealant to cure fully before use.

SOLD SEPARATELY

Pan connector or waste adaptor, isolation valve, installation fixings, sealants and plumbing connections are sold separately unless expressly included in the order.

These instructions provide general guidance. The current Bathco technical specification and the instructions for every selected installation system take precedence.