

INSTALLATION INSTRUCTIONS

Antequera Matt Black Wall-Hung Rimless WC | Product code: BAT4561

Before you begin

Installation must be completed by a competent installer in accordance with local building and plumbing requirements. Inspect the WC and compare it with the current technical specification before fitting. Do not install a damaged product.

Confirm the installation

This wall-hung WC requires a compatible concealed WC frame and cistern. The supporting system—not the finished wall surface—must carry the full design load. Confirm the frame rating, flush plate, outlet position, finished wall build-up and 485 x 355 x 320 mm WC dimensions before installation.

- 1 Select the system. Confirm the concealed frame, cistern, flush plate, mounting hardware and waste connector are mutually compatible and suitable for the wall construction.
- 2 Install the frame. Fix, plumb and level it to suitable structural floor and wall elements in accordance with the frame manufacturer's instructions and local requirements.
- 3 Set services and projections. Position the flush pipe, waste connector and mounting studs for the completed wall thickness and the Bathco technical specification.
- 4 Complete and inspect the wall. Pressure-test and flush the concealed system before closing the wall; retain service access through the flush-plate opening.
- 5 Fit the WC. Protect the porcelain, trim connection pipes accurately, fit seals and slide the pan evenly onto the studs without forcing or point-loading it.
- 6 Secure and seal. Tighten fixings evenly to the system manufacturer's torque guidance and apply neutral-cure sanitary silicone at the wall junction, leaving any required drainage gap.
- 7 Commission. Flush repeatedly, inspect every accessible connection for leaks, confirm stable mounting, and fit and adjust the supplied soft-close seat and cover.

SOLD SEPARATELY

Compatible concealed WC frame, cistern, flush plate, connection components, installation fixings, sealants and plumbing connections are sold separately unless expressly included in the order.

These instructions provide general guidance. The current Bathco technical specification and the instructions for every selected installation system take precedence.